

Model: i

- Viewable size is 21.6"
- High quality, space-saving 21.6-inch wide display with height adjust, swivel and tilt stand
- 1920 x 1080 resolution delivers sharp images
- Extra wide 170-degree (horizontal) x 160-degree (vertical) viewing angles
- Slim, lightweight profile allows easy handling and saves desk space
- Built-in speakers eliminate need for separate desktop speakers
- Standard analog and DVI digital interfaces
- Energy-saving design consumes less than half the power of traditional CRTs



Panel

Type:	21.6-inch Wide Active Matrix TFT (thin film transistor)
Viewable Image Area:	21.6 inch wide, Anti Glare
Active Area:	477.5(H) mm x 268.6(V) mm
Native Resolution:	WSXGA+ 1920 x 1080
Viewing Angle:	H: 170 Degrees V : 160 Degrees
Pixel Pitch:	0.248mm*0.248mm
Brightness*:	Up to 300 nits (cd/m ²)
Contrast Ratio*:	Up to 1000:1
Response Rate*:	5ms (typical rise + fall)
Colour Depth Support:	16.7 million colours

On Screen Display (OSD) Controls

Buttons/Switches:	OSD (On screen display) Power on/off
Languages:	English, French, Spanish
User Controls:	Brightness Contrast Auto Contrast Horizontal Position Vertical Position OSD Timeout Factory Reset

Video Performance

Horizontal Frequency:	FH: 55 – 75Hz
Vertical Frequency:	FV: 56-75Hz
Multimode Supported:	PC Compatibles (up to 1920 x 1080 Non Interlaced)

Video Input

Plug and Play:	yes - DDC1 & DDC2B
Input Signal:	(Dual) 15-pin mini D-sub VGA + 24-pin Digital DVI-D (Cables included)

Audio

Stereo Input Jack:	yes
Stereo Cable:	Included
Sound Output:	1 Watt per Channel (2 x Speakers)

Power

Power Supply:	100 - 240 VAC, 50/60 Hz
Power Management:	VESA DPMS –
Power Consumption:	On: 49W (max.)/Off: 1W (max.)

Dimensions and Weight

Dimensions:	512.7(W) x 401.1(H) x 250.0(D) mm
Weight:	6.3 kg
Carton Dimensions:	565(W) x 209(H) x 477(D) mm

Height Adjustable Stand

21.6 inch monitor with stand: 6.3kg
 Height Adjustment Range: 110mm +/- 4mm
 Tilt Adjustment – Up Angle: 18 +/- 2 degrees
 Tilt Adjustment – Down Angle -3 +/- 2 degrees
 Landscape to Portrait: 90 degrees +2/-0
 Side to Side Pan: 170 +/- 2 degrees left and right

Security

Cable lock slot	Yes (Kensington Lock)
-----------------	-----------------------

Environmental Specifications

Operating Temperature:	0° to 40° C
Operating Humidity:	15% to 90%
Non Operating Temperature:	-20° to 60° C
Non Operating Humidity:	15% to 90%

Certification and Compliance

Safety:	UL, cUL, CB
EMI:	FCC, IC, CE, C-Tick
Environment :	RoHS, EPEAT
Compatibility:	VESA Standard

In the Box

- 1 x User's Manual
- 1 x Power Cable
- 1 x 15 pin D-sub Cable
- 1 x Audio Cable
- 1 x DVI-D Cable

Canadian Limited Warranty

This Toshiba Flat Panel Display comes with a three (3) year parts and labour Limited Warranty.

Part Number/UPC code

PA3768C-1LCH /883974235421

ⁱToshiba of Canada Limited Information Systems Group shall not be liable for damages of any kind for use of this information, which is subject to change without notice.

Subject to Change:

While Toshiba has made every effort at the time of publication to ensure the accuracy of the information provided herein, product specifications, configurations, prices, system/component/options availability are all subject to change without notice. All performance specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all Toshiba's component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower. For the most up-to-date product information, or to stay current with the various options, visit Toshiba's website at toshiba.ca

1/18/2010 v.1